



台灣塑膠工業股份有限公司麥寮廠

To buy, visit us at www.jitsy.in 1

Formosa Plastics Corporation

Mailiao Plant: NO.1, Formosa Industrial Complex,

Mailiao Village, Yunlin County, Taiwan

Tel: 886-5-681-2345 Fax: 886-2-681-2833

Technical Data Sheet

Taisox 7350M

1. Product description

7350M is an ethylene/vinylene acetate copolymer. The trade name is Taisox. This product is manufactured by the high-pressure process. By incorporating vinyl acetate (VA) into the ethylene chain, the high-pressure process produces co-polymerization to EVA.

7350M is a general-purpose for X-linked foam shoes, mid-sole, gaskets. It provides good chemical resistance, excellent elasticity, and high flexible properties.

2. Typical properties

To buy, visit us at www.jitsy.in

| Properties | Units | Test Method | Typical Value |
|---------------------------|--------------------|-------------|---------------|
| Melt Index $MI_{2.16}$ | g/10min | ASTM D1238 | 2.5 |
| Density | g/cm ³ | ASTM D1505 | 0.938 |
| Vinyl Acetate content | % | FPC method | 18 |
| Thermal properties | | | |
| Melting point | | DSC | 84 |
| Brittleness point | | ASTM D746 | <-70 |
| Softening point | | ASTM D1525 | 60 |
| Mechanical properties | | | |
| Tensile strength at yield | Kg/cm ² | ASTM D638 | 45 |
| Tensile strength at break | Kg/cm ² | ASTM D638 | 150 |
| Elongation at break | % | ASTM D638 | 800 |
| Hardness | Shore A | ASTM D2240 | 88 |
| Hardness | Shore D | ASTM D2240 | 38 |

*Data shown are average values and should not be examined for specifications

3. Regulatory status

The grade meets the specification promulgated by the Food and Drug Administration of United States of America (FDA) for olefin polymers in 21 code of Federal Regulation Section 177.1350 and gets the certification of RoHS(the restriction of the use of certain hazardous substances in electrical and electronic equipment). Please contact your Formosa Plastics corporation representative for detailed information and other documents. More details, Please browse our website: www2.fpc.com.tw/pe/indexe.

4. Packing

FPC supplied in 25Kg/paper bag or bulk bag.

5. Storing

EVA must be stored at temperature under 40°C. The sun radiation, heat, humidity is prohibit.

The expiration date is 3 years.

Last Update: January 7, 2022

To buy, visit us at www.jitsy.in